



FIELDBOOK · TABLET

Fieldbook N101 Tablet

Industries: Industry · Logistics · Public safety

Operating system Android® 9.0 Pie, Google Zero Touch compatible, full access to the Google Play Store



IP67

IP RATING

450 nits

BRIGHTNESS

970 g

WEIGHT

CORE SPECIFICATIONS

Display size	10.1 inch
Resolution	1920 x 1200
IP rating	IP67
MIL-STD	-
Brightness	450 nits
Processor	Qualcomm® SDM632, Kryo™ 250 octa-core, 1.8 GHz
Memory and storage	4 GB RAM · 64 GB internal storage
Battery	Hot-swappable, 11,700 mAh + 4,000 mAh, 3.7 V
Weight	970 g
Operating temperature	-20 °C to +60 °C
Interfaces	2× USB 2.0 Type-A · 1× USB-C OTG · 1× audio jack · 1× external coax antenna · 1× TF card slot · 1× micro-HDMI · 2× nano-SIM · 1× external GPS antenna connector (PIFA) · 2× POGO interface connector
Configurable	No – The manufacturer datasheet lists exactly one option (barcode scanner, optional), too few for a configurator.

Source for display size to interfaces (eleven core rows): manufacturer datasheet (Logic Instrument, as at 14 January 2020, French). MIL-STD is not quantified there and stays "-". Source for configurability: comparison table: tablets (German) (unchanged, not a manufacturer property).

INTERFACES

- 2× USB 2.0 Type-A
- 1× audio jack
- 1× USB-C OTG
- 1× external coax antenna



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985

- 1× TF card slot
- 2× nano-SIM
- 2× POGO interface connector
- 1× micro-HDMI
- 1× external GPS antenna connector (PIFA)

CERTIFICATIONS AND RUGGEDNESS

IP67

FEATURES AND OPTIONS

Operating system	Android® 9.0 Pie, Google Zero Touch compatible, full access to the Google Play Store
Screen	IPS technology, 10-point multi-touch, dual-mode capacitive, heat-tempered glass
Barcode scanner (optional)	integrated 1D/2D EM2096 scanner
Expansion slot	GNSS/LoRa/AV-IN/CAN/UART as well as USB/UART/I2C/GPIO/CAN
Cameras	5 MP front camera, 13 MP rear camera (Sony) with flash LED
Certifications per manufacturer description	IP67, CE, WEEE, RoHS; drops from 1.2 m height

MANUFACTURER DATASHEET

Logic Instrument, as at 14 January 2020 · binding source

[fieldbook-NI01.Spec-Sheet-v1-FR.pdf](#)

This overview was compiled from the documented information and is not a manufacturer datasheet. The manufacturer's specifications are binding. Subject to change, errors reserved, technical developments subject to change. As at: 8 August 2026.



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985