



FIELDBOOK · TABLET

Fieldbook N101G2 Tablet

Industries: Industry · Logistics · Public safety
Operating system Android 14 with Google services (GMS)



IP65
IP RATING

810H
MIL-STD

700 nits
BRIGHTNESS

1.140 kg
WEIGHT

CORE SPECIFICATIONS

Display size	10.1 inch
Resolution	1200 x 1920
IP rating	IP65
MIL-STD	MIL-STD-810H
Brightness	700 nits
Processor	Helio G99, 2× Arm Cortex-A76 (up to 2.2 GHz), 6× Arm Cortex-A55 (up to 2 GHz)
Memory and storage	8 GB LPDDR4 RAM · 128 GB eMMC
Battery	3.8 V / 10,000 mAh, replaceable without tools
Weight	1.140 kg
Operating temperature	-20 °C to +60 °C
Interfaces	1× USB Type-C · 1× USB Type-A · 1× RJ45 LAN · 1× microSD · 1× nano-SIM · 1× POGO for docking station · 1× 3.5 mm audio jack
Configurable	Yes, interactive configurator on the product page (3 groups)

Source for display size to interfaces (eleven core rows): manufacturer datasheet (Logic Instrument, as at 13 June 2024). Source for "Configurable": interactive configurator on the product page , based on the manufacturer datasheet (see source per option there).

INTERFACES

- 1× USB Type-C
 - 1× RJ45 LAN
 - 1× nano-SIM
- 1× USB Type-A
 - 1× microSD
 - 1× POGO for docking station



REQUEST QUOTATION
Scan the QR code or call – configuration, quantities, and delivery time on request.
kontakt@robustbook.com | +49 (0) 69 271 470 985

– 1× 3.5 mm audio jack

CERTIFICATIONS AND RUGGEDNESS

MIL-STD-810H

Shock, vibration, temperature, altitude

IP65

FEATURES AND OPTIONS

Operating system	Android 14 with Google services (GMS)
Screen	IPS, protected by 7H hardened glass, sunlight-readable, capacitive touchscreen
Connectivity	Wi-Fi 6 (802.11 a/b/g/n/ac), Bluetooth 5.2
Options per manufacturer description	Zebra SE4710 1D/2D barcode reader, serial RS232 port on DB9 (as a replacement for RJ45), additional USB Type A port (as a replacement for RJ45)
Accessories	desktop docking station with battery charger, vehicle charging station
Certifications per manufacturer description	IP65, MIL-STD-810H, CE, RoHS; drops from up to 1.2 m height
Scope of delivery (per manufacturer datasheet)	Fieldbook N101G2 tablet, battery, 18 W AC power adapter, USB Type-C cable, handstrap, quick start guide

CONFIGURATION OPTIONS

READERS AND SECURITY

1D/2D barcode scanner Zebra SE4710 [\[DB\]](#)

INTERFACES AND MODULES

DB9 serial port RS232 (replaces LAN/RJ45) [\[DB\]](#)

Additional USB 2.0 port (replaces LAN/RJ45) [\[DB\]](#)

ACCESSORIES

Office docking station with battery charger [\[DB\]](#)

Vehicle docking station [\[DB\]](#)

db Fieldbook N101G2 manufacturer datasheet, Logic Instrument, as at 13.06.2024, English, /datasheets/EN/Logic-Instrument_Fieldbook_N101G2_EN_v1.pdf

MANUFACTURER DATASHEET

Logic Instrument, as at 13 June 2024 · binding source

[Logic-Instrument_Fieldbook_N101G2_EN_v1.pdf](#)

This overview was compiled from the documented information and is not a manufacturer datasheet. The manufacturer's specifications are binding. Subject to change, errors reserved, technical developments subject to change. As at: 8 August 2026.



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985