



FIELDBOOK · TABLET

Fieldbook P122G2 Tablet

Industries: Industry · Construction · Logistics
Operating system Windows 11 Pro



IP65
IP RATING

810G
MIL-STD

650 nits
BRIGHTNESS

1,600 g
WEIGHT

CORE SPECIFICATIONS

Display size	12.2 inch
Resolution	1920 x 1200
IP rating	IP65
MIL-STD	MIL-STD-810G
Brightness	650 nits
Processor	Intel® Core™ i7-1255U
Memory and storage	16 GB RAM · 128 GB SSD (further storage options available per the manufacturer datasheet, without specific capacities stated)
Battery	7.4 V / 6,300 mAh, replaceable without tools; backup battery 7.4 V / 700 mAh
Weight	1,600 g
Operating temperature	-20 °C to +60 °C
Interfaces	USB Type-C 3.0 × 1 · USB Type-A 3.0 × 1 · Micro SD × 1 · SIM × 1 · RJ45 (Gigabit Ethernet) × 1 · Mini-HDMI 2.1A × 1 · POGO (docking station) × 1 · 3.5 mm audio × 1 · DC-in × 1 Optional: RS232 (Sub-D9, replaces RJ45), USB 2.0 Type A (replaces RJ45), N3680 1D/2D barcode scanner
Configurable	Yes, interactive configurator on the product page (3 groups)

Source for display size to interfaces (eleven core rows): manufacturer datasheet (Logic Instrument, as at 07 December 2023, French). Source for "Configurable": interactive configurator on the product page , based on the manufacturer datasheet (see source per option there).

INTERFACES

- USB Type-C 3.0 × 1
- USB Type-A 3.0 × 1



REQUEST QUOTATION
Scan the QR code or call – configuration, quantities, and delivery time on request.
kontakt@robustbook.com | +49 (0) 69 271 470 985

- Micro SD × 1
- RJ45 (Gigabit Ethernet) × 1
- POGO (docking station) × 1
- DC-in × 1
- SIM × 1
- Mini-HDMI 2.1A × 1
- 3.5 mm audio × 1

Optional: RS232 (Sub-D9, replaces RJ45), USB 2.0 Type A (replaces RJ45), N3680 1D/2D barcode scanner

CERTIFICATIONS AND RUGGEDNESS

MIL-STD-810G

IP65

FEATURES AND OPTIONS

Operating system	Windows 11 Pro
Camera	2 MP front / 8 MP rear camera with autofocus
Connectivity	Wifi 6, Bluetooth 5.1, LTE FDD/TDD, WCDMA, GPS, NFC
Security	TPM 2.0, fingerprint reader
Optional (replaces the RJ45 port)	N3680 1D/2D barcode scanner, RS232 on Sub-D9, USB 2.0 Type A
	Drop-tested to 1.2 m height per manufacturer datasheet
Scope of delivery (per manufacturer datasheet)	tablet, digitizer pen with battery, AC/DC power adapter, back strap, carrying handle, shoulder strap, USB Type-C cable, user manual

CONFIGURATION OPTIONS

READERS AND SECURITY

1D/2D barcode scanner N3680 (replaces RJ45) [\[DB\]](#)

INTERFACES AND MODULES

RS232 on DSUB 9 connector (replaces RJ45) [\[DB\]](#)

USB 2.0 Type A connector (replaces RJ45) [\[DB\]](#)

ACCESSORIES

Quad slots battery charger [\[DB\]](#)

Car charger [\[DB\]](#)

Handstrap [\[DB\]](#)

Office docking station with battery charger [\[DB\]](#)

Vehicle docking station with ports replicator [\[DB\]](#)

db Fieldbook P122G2 manufacturer datasheet, Logic Instrument, as at 07.12.2023, French, /datasheets/FR/Logic-Instrument_Fieldbook_P122G2_V02_FR.pdf

MANUFACTURER DATASHEET

Logic Instrument, as at 07 December 2023 · binding source

[Logic-Instrument_Fieldbook_P122G2_V02_FR.pdf](#)

This overview was compiled from the documented information and is not a manufacturer datasheet. The manufacturer's specifications are binding. Subject to change, errors reserved, technical developments subject to change. As at: 8 August 2026.



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985