



GETAC · TABLET (EXPLOSION-PROTECTED)

Getac UX10-EX Tablet

Industries: Industry · Public Safety

Explosion protection Certified to ATEX/IECEX Zone 2/22 – "Ex II 3G Ex ic op is IIC T4 Gc" and "Ex II 3D Ex ic op is IIIC T130°C Dc" (quoted verbatim from the manufacturer datasheet, "Explosion Protection" section)



IP66

IP RATING

810H

MIL-STD

1,000 nits

BRIGHTNESS

1.38 kg

WEIGHT

CORE SPECIFICATIONS

Display size	10.1 inch
Resolution	WUXGA (1920 x 1200)
IP rating	IP66
MIL-STD	MIL-STD-810H
Brightness	1,000 nits
Processor	Intel® Core™ i5-1235U (12th generation), up to 4.4 GHz with Intel® Turbo Boost, 12 MB Smart Cache (optional Intel® Core™ i5-1245U vPro® up to 4.4 GHz, i7-1255U up to 4.7 GHz, or i7-1265U vPro® up to 4.8 GHz)
Memory and storage	8 GB DDR4 RAM (optional 16 GB or 32 GB DDR4) · 256 GB PCIe NVMe SSD (optional 512 GB or 1 TB PCIe NVMe SSD)
Battery	Li-ion smart battery 11.1V, typical 4,200 mAh (min. 4,080 mAh) x 1 (optional high-performance battery 10.8V, 9,240 mAh x 1)
Weight	1.38 kg
Operating temperature	0 °C to 55 °C
Interfaces	5MP webcam x 1 · 8MP auto focus rear camera x 1 · audio in/out combo x 1 · DC in jack x 1 · USB 3.2 Gen 2 Type-A x 1 · Thunderbolt™ 4 Type-C x 1 (optional Windows Hello face-authentication camera, optional SIM card slot Micro-SIM/3FF)
Configurable	Yes, interactive configurator on the product page (8 groups)

Source for core specifications (except "Configurable"): manufacturer datasheet Getac UX10-EX (PDF, as at 06 August 2026, see note above). Source for "Configurable": interactive configurator on the product page , based on the manufacturer datasheet (see source per option there).

INTERFACES

- 5MP webcam x 1

– 8MP auto focus rear camera x 1



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985

- audio in/out combo x 1
- USB 3.2 Gen 2 Type-A x 1
- DC in jack x 1
- Thunderbolt™ 4 Type-C x 1 (optional Windows Hello face-authentication camera, optional SIM card slot Micro-SIM/3FF)

CERTIFICATIONS AND RUGGEDNESS

MIL-STD-810H

Shock, vibration, temperature, altitude

IP66

Completely dustproof, jet water resistant

FEATURES AND OPTIONS

Explosion protection	Certified to ATEX/IECEX Zone 2/22 – "Ex II 3G Ex ic op is IIC T4 Gc" and "Ex II 3D Ex ic op is IIIC T130°C Dc" (quoted verbatim from the manufacturer datasheet, "Explosion Protection" section)
Display	LumiBond® technology, capacitive dual mode touchscreen (multi-touch and digitizer)
Connectivity	Intel® Wi-Fi 6E AX211 · Bluetooth 5.3 · optional 5G Sub-6 or 4G LTE mobile broadband with integrated GPS · Dual SIM (Micro-SIM 3FF and e-SIM)
Ruggedness	drop-resistant to 1.8 m, vibration-resistant
Security	TPM 2.0, optional Intel® vPro®, optional HF RFID reader, optional Windows Hello facial recognition
	3-year Bumper-to-Bumper warranty per the manufacturer datasheet (Getac's commitment, not a Robustbook service)

CONFIGURATION OPTIONS

PROCESSOR

Standard: Intel® Core™ i5-1235U Processor, up to 4.4 GHz with Intel® Turbo Boost Technology, 12 MB Intel® Smart Cache^[DB]

Intel® Core™ i5-1245U vPro® Processor, up to 4.4 GHz with Intel® Turbo Boost Technology, 12 MB Intel® Smart Cache^[DB]

Intel® Core™ i7-1255U Processor, up to 4.7 GHz with Intel® Turbo Boost Technology, 12 MB Intel® Smart Cache^[DB]

Intel® Core™ i7-1265U vPro® Processor, up to 4.8 GHz with Intel® Turbo Boost Technology, 12 MB Intel® Smart Cache^[DB]

MEMORY

Standard: 8 GB DDR4 ^[DB]

16 GB DDR4 ^[DB]

32 GB DDR4 ^[DB]

STORAGE

Standard: 256 GB PCIe NVMe SSD ^[DB]

512 GB PCIe NVMe SSD ^[DB]

1 TB PCIe NVMe SSD ^[DB]

APPROVALS

Standard: ATEX/IECEX Zone 2/22 certified for use in hazardous areas (Ex II 3G Ex ic op is IIC T4 Gc, Ex II 3D Ex ic op is IIIC T130°C Dc)^[DB]

WIRELESS AND POSITIONING

Standard: Intel® Wi-Fi 6E AX211 (802.11ax), Bluetooth v5.3, Dual-SIM (microSIM 3FF and e-SIM)^[DB]

5G Sub-6 with integrated GPS and SIM card slot (Micro-SIM, 3FF)^[DB]

4G LTE mobile broadband with integrated GPS and SIM card slot (Micro-SIM, 3FF)^[DB]

READERS AND SECURITY

Intel® vPro® Technology ^[DB]

HF RFID reader ^[DB]

Windows Hello face authentication camera (front-facing), mutually exclusive with the 5M webcam^[DB]

1D/2D imager barcode reader (Expansion slot top)^[DB]

Absolute Persistence ^[DB]



REQUEST QUOTATION

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | +49 (0) 69 271 470 985

BATTERY AND POWER

High-performance battery (10.8 V, 9240 mAh) x 1 [\[DB\]](#)

ACCESSORIES

Power adapter, 100 W, 100-240 VAC [\[DB\]](#)

Multi-bay charger, two bays [\[DB\]](#)

Multi-bay charger, eight bays [\[DB\]](#)

Digitizer stylus (spare) [\[DB\]](#)

Anti-statische Screen protector [\[DB\]](#)

Shoulder strap (2-Punkt) [\[DB\]](#)

Shoulder strap (4-Punkt; Freihandbedienung) [\[DB\]](#)

Rotating hand strap with kickstand [\[DB\]](#)

db Getac UX10-EX (generation G3) manufacturer datasheet, PDF as at 06 August 2026, /datasheets/EN/Getac_UX10G3-EX_EN_Product.pdf

MANUFACTURER DATASHEET

Getac, as at 06 August 2026 · binding source

[Getac_UX10G3-EX_EN_Product.pdf](#)

This overview was compiled from the documented information and is not a manufacturer datasheet. The manufacturer's specifications are binding. Subject to change, errors reserved, technical developments subject to change. As at: 8 August 2026.

**REQUEST QUOTATION**

Scan the QR code or call – configuration, quantities, and delivery time on request.

kontakt@robustbook.com | **+49 (0) 69 271 470 985**